



**(43) International Publication Date**  
**14 July 2005 (14.07.2005)**


## PCT

**(10) International Publication Number**  
**WO 2005/063558 A1**

- |   |   |
|---|---|
| <b>(51) International Patent Classification<sup>7</sup>:</b>  | <b>(81) Designated States</b> ( <i>unless otherwise indicated, for every kind of national protection available</i> ): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW. |
| <b>(21) International Application Number:</b>   |   |
|   |   |
| <b>(22) International Filing Date:</b>  |   |
|   |   |
| <b>(25) Filing Language:</b>  |   |
| <b>(26) Publication Language:</b>   |   |
| <b>(30) Priority Data:</b>  | <b>(84) Designated States</b> ( <i>unless otherwise indicated, for every kind of regional protection available</i> ): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).  |
| 0303589-6   |   |
| 30 December 2003 (30.12.2003)   |   |
| <b>(71) Applicant and</b>   |   |
| <b>(72) Inventor: NORRMAN, Jan</b> [SE/SE]; Ytterbyvik 3, S-185 94 Vaxholm (SE).                            |   |
| <b>(74) Agents: SUNDSTRÖM, Per</b> et al.; Stenhagen Patentbyrå AB, P.O. Box 4630, S-116 91 Stockholm (SE). |   |

[Continued on next page]

- (54) Title:** A CONTROL DEVICE FOR A MOTOR VEHICLE



- (57) Abstract:** An automotive vehicle, such as a motorcycle, has an electric ignition system for igniting fuel delivered to the engine of the vehicle, and a rotatable handle which the driver holds in one hand when driving the vehicle and rotates to control the power output of the engine between an idling end position and a high power end position. The device includes a switch (80) for cutting out the ignition system (72) temporarily. This is achieved by turning the handle (2) towards and beyond a yieldable engine-idling abutment (63), by exerting a strong torque that exceeds a pre-chosen value.



**Declaration under Rule 4.17:**

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*